



**Luminaire Efficiency: 96.7%**

### Life/ Maintenance

- |                                 |                              |
|---------------------------------|------------------------------|
| • LED Driver Average Rated Life | 50 000hrs                    |
| • LED Life                      | 50 000hrs (L80 F10, TP 45°C) |

### Application

- |                  |                                   |
|------------------|-----------------------------------|
| • Retail Stores  | • Hotels                          |
| • Shopping Malls | • Interior Architectural Lighting |

### Benefits

- **5 Year warranty**
- Built-in surge Protection

### Product Features and Accessories

- High colour rendering index CRI > 80 (CRI >90 available on request)
- Colour temperature 4000K (3000K on request)
- Small colour tolerance - MacAdam 3
- Special colours on request
- Powder coated aluminium body
- Available in wide and narrow beam angle (34° and 19°)
- Higher wattage and output available on request

Specification	Lumen @ 45°C	System Power	Power Factor	Current	Dimensions			Weight
					H	L	D	
M18-12W	2115	14.2W	0.98	350mA	200mm	110mm	89mm	1kg
M18-17W	2950	20.9W	0.98	500mA	200mm	110mm	89mm	1kg
M18-25W	4010	28.6W	0.98	700mA	200mm	110mm	89mm	1kg