


Luminaire Efficiency: 90.7%
Life/ Maintenance

| | |
|---------------------------------|------------------------------|
| • LED Driver Average Rated Life | 50 000hrs |
| • LED Life | 55 000hrs (L80 F10, TP 45°C) |

Application

| | |
|--------------|-------------------|
| • Hotels | • Residential |
| • Apartments | • Treatment Rooms |

Benefits

- **5 Year warranty**
- Built-in surge Protection

Product Features and Accessories

- High colour rendering index CRI > 80 (CRI > 90 on request)
- Colour temperature 4000K and 3000K available
- Direct replacements for 50W to 75W low voltage halogen fixtures
- Available in wide and narrow beam (34° and 18°)
- Fully dimmable version on request
- Tridonic COB and driver
- Ripple current < 3%
- All fixtures component parts are replaceable
- Non-corrosive bezel
- Fits into existing cut out of 100 to 115mm

| Specification | Lumen @ 45°C | System Power | Power Factor | Current | Dimensions | | | Weight |
|------------------|--------------|--------------|--------------|---------|------------|-------|-------|--------|
| | | | | | Cut Out | D | H | |
| FUT4-7W-LED-840 | 1080 | 7.8W | 0.98 | 180mA | 100mm | 130mm | 100mm | 0.5kg |
| FUT4-11W-LED-840 | 1740 | 12.6W | 0.98 | 300mA | 100mm | 130mm | 100mm | 0.5kg |